

MC247N 150KWe



ENERSI Green Technologies for energy & environment

SPECIFICATIONS	standby power	KVA/KWe	275/220
	prime power	KVA/KWe	250/200
	continuous power	KVA/KWe	188/150
	thermal power	KWt	216
	frequency	Hz	50
	rated voltage	V	400
	rated current	A	360,9
	power factor	COSΦ	0,8
	noise level @1mt full load	dBA	68
ENGINE	model	—	M- Cummins NTAA855
	displacement	L	14
	speed	RPM	1500
	compression ratio	—	10:1
	bore*stroke	mm*mm	140*152
	starting method	—	electric start
	jacket water cooling	—	water cooled
	exhaust manifold	—	water cooled
	oil capacity	L	36
	oil cooler	—	yes
	mixer	—	IMPCO, USA
	ignition system	—	made in Canada
	speed governor	—	WOODWARD
ALTERNATOR	model	—	LSA 46.2 L6
	phase	—	3 phases, 4 wires
	connecting method	—	SAE standard
	way of excitation	—	brushless, self-excitation
	insulation grade	—	H level
GENERATOR SET	controller cabinet	—	9902
	controller type	—	ComAp Controller IL-NT-MRS10
	fuel	—	PNG/CNG/LNG
	gas inlet pressure (MAX)	kPa	6
	protection level	—	IP23
	warranty period	—	4000 hrs or 2 years
	NG consumption @full load	NMC/h	48
DIM.	dimension	mm*mm*mm	2900*1200*1850
	net weight	kg	2200